



Unmanned Vehicle Guidance Using Video Camera/Vehicle Model

**(MSFC Center Director's Discretionary Fund Final Report,
Project No. 97-23)**

T. Sutherland

Marshall Space Flight Center, Marshall Space Flight Center, Alabama

The NASA STI Program Office...in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results...even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
NASA Access Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320



Unmanned Vehicle Guidance Using Video Camera/Vehicle Model

**(MSFC Center Director's Discretionary Fund Final Report,
Project No. 97-23)**

T. Sutherland

Marshall Space Flight Center, Marshall Space Flight Center, Alabama

National Aeronautics and
Space Administration

Marshall Space Flight Center • MSFC, Alabama 35812

Available from:

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
(703) 487-4650

TABLE OF CONTENTS

1.	INTRODUCTION	1
2.	DESCRIPTION	2
3.	APPROACH.....	4
4.	DEVELOPMENT	5
5.	ADVANCED VIDEO GRAPHICS ADAPTER SYSTEM SPECIFICATIONS	7
	5.1 Hardware	7
	5.2 Software	7
6.	CONCLUSION.....	8
7.	FUTURE WORK	8
	REFERENCES	9

LIST OF FIGURES

1.	Docking scenario for the basic VGS system	1
2.	Current VGS system configuration	2
3.	Current VGS image resolution—images as seen and after processing	3
4.	VGS analog section	3
5.	VGS C40 main and video mezzanine boards	5
6.	Advanced VGS new camera configuration	6
7.	Advanced VGS system overview	6

LIST OF ACRONYMS

CCD	charged coupled device
CDDF	Center Director's Discretionary Fund
DSP	digital signal processor
EEPROM	electronically erasable programmable read only memory
EXVM	experimental vector magnetograph
FFT	fast fourier transform
FPGA	field programmable gate arrays
NT	new technology
RAM	random access memory
STS	Space Transportation System
UART	universal asynchronous receiver/transmitter
VGS	video guidance sensor
VME	versa module eurocard

TECHNICAL MEMORANDUM

UNMANNED VEHICLE GUIDANCE USING VIDEO CAMERA/VEHICLE MODEL (Center Director's Discretionary Fund Final Report, Project No. 97-23)

1. INTRODUCTION

The purpose of this Center Director's Discretionary Fund (CDDF) project was to improve the state of the art of vehicle navigation by two methods: (1) Improve current video guidance sensor (VGS) capabilities by redesigning the video sensor assembly; and (2) create an algorithm development system that could be used to produce a camera/vehicle modeling method for vehicle tracking. Figure 1 depicts the docking scenario for the basic VGS system.




Figure 1. Docking scenario for the basic VGS system.

2. DESCRIPTION

Figure 2 depicts the VGS system which flew on STS-87 and STS-95. This system uses a single camera as the imaging device. Two successive images are captured with each image scene. For example, the target vehicle with retroreflector is illuminated by two lasers of different frequencies. The two images will be the same except that the retroreflectors have a filter over them that absorbs one of the laser frequencies. The difference image, created by subtracting the two images, only reveals the targets and no other objects. Figures 3 and 4 demonstrate this difference image process. By knowing the dimensions of targets and their relative positions, the relative position of the camera can be computed. This current configuration can only support a navigation update rate of 5 Hz due to the heavy burden of image subtraction.

Limitations and restrictions of the current VGS system are as follows:

- It requires target vehicle to be fitted with a group of retroreflectors.
- The target vehicle viewing angle is very limited.
- Other types of guidance must be used to maneuver the target into a good viewing angle.
- The update rate is limited by hardware and software tasks.




Figure 2. Current VGS system configuration.




Figure 3. Current VGS image resolution—images as seen and after processing.




Figure 4. VGS analog section.

3. APPROACH

Three methods were used to improve the current VGS:

- Implementation of the image subtraction algorithm was accomplished using hardware to speed up the navigation update rate. A typical example would be a subtractor using a memory lookup table and field programmable gate arrays (FPGA's).
- Development of both the hardware to implement image acquisition and the software/algorithm development system.
- Optimization of the hardware/software development platform to allow for development and testing to determine the best algorithm that would allow tracking and coordinate acquisition using a single camera/nontarget based system.

4. DEVELOPMENT

The first 2 yr have been dedicated to designing electronic hardware, selecting optical components, and literature searches. A TMS320C40 digital signal processor (DSP) based processing card was designed and built. The DSP board can accept an optional daughter card for specific design applications. This board has already been adapted to work on another CDDF project, the Experimental Vector Magnetograph (EXVM) Experiment, as the heart of the video processor system, thus proving the usefulness of the DSP/daughter card concept. The EXVM video processing system uses two DSP boards and two special purpose video interface daughter cards. Figure 5 depicts the TMS320C40 system.




Figure 5. VGS C40 main and video mezzanine boards.

Two additional video interface daughter cards have been built for the CDDF project pertaining to this paper. One card takes the Wavelet transform of the image in hardware using a dedicated Wavelet transform chip. The second daughter card has been developed with the capability to digitize one or two camera inputs. This card can be configured to read and store camera inputs or preprocess images before passing data to the DSP for further processing. Preprocessing is accomplished in an FPGA. Types of preprocessing include edge detection, background and image subtraction, and possibly fast Fourier transform (FFT).

Methodologies for vehicle tracking have been studied and have been incorporated into the design of the model-based vehicle tracking system. One approach to vehicle attitude determination is using an

aspect ratio calculation. The aspect ratio of image data is calculated and compared to a database of precalculated aspect ratio calculations. A “best fit” is determined by comparison of peaks in the aspect data. This method needs further investigation and may be combined with other methodologies such as “feature space trajectories.”¹ Figures 6 and 7 depict the advanced VGS camera configuration and system overview.




Figure 6. Advanced VGS new camera configuration.




Figure 7. Advanced VGS system overview.

5. ADVANCED VIDEO GRAPHICS ADAPTER SYSTEM SPECIFICATIONS

5.1 Hardware

- TMS320C40 Texas Instrument® DSP board
- 50 MHz (40-ns instruction time)
- 128k words of local static RAM
- 512 kbytes of boot electronically erasable programmable read only memory (EEPROM) (reprogrammable on board)
 - Universal Asynchronous receiver/transmitter for serial communications
 - Full 6U, 32-bit versa module eurocad (VME) interface
 - Interface for mezzanine board
 - Video interface mezzanine board
 - 128 kbytes of static RAM
 - Dual camera inputs, accepts RS-170 or National Television Standard's Committee video input
 - Subtraction of images done by EEPROM lookup table via FPGA
 - Video passes through an FPGA for additional processing capabilities.
- Pentium-based VME bus computer
 - Running Windows NT²
 - Full VME master controller/interface.

5.2 Software

- MATLAB³ v5.3 used for algorithm development and VME interfacing
 - Algorithm development
 - C-development platform
 - Graphical user interface for development platform.
- C++ Language on Windows NT® running under MATLAB
 - C running on the TMS320C40 DSP
 - Assembly language running on the TMS320C40 DSP.

6. CONCLUSION

The design of the entire VGS development system was a learning experience. The development scope of the system consisted of two areas: (1) Hardware construction and testing, and (2) research into providing the best resources for this type of work. The system that was produced has already been used on another EXVM project and will probably provide other projects with the groundwork for getting started. The development system can provide a platform for many areas of research, not limited to navigation. The ability to develop algorithms and to test them in real hardware is a needed resource and can be only one step away from having a space-qualified platform.

7. FUTURE WORK

The system for development of a model-based tracking system has been established. The combination of the dual-camera concept and model-based tracking system needs to be further developed so that a robust and adaptable vision guidance system will be available for current and future guidance applications. Although further algorithm development and improvement is lacking, hardware to implement and test the model-based algorithm is now available.

REFERENCES

1. Casasent, D.; and Sipe, M.: "Feature Space Trajectory Representation and Processing for Active Vision," *SPIE Vol. 2904*—8, 1996.
2. *Windows NT V4.0*, Microsoft Corp., 1996.
3. *MATLAB*, The Mathworks, Inc., 1996.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operation and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503				
1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE December 1999		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE Unmanned Vehicle Guidance Using Video Camera/Vehicle Model (MSFC Center Director's Discretionary Fund Final Report, Project No. 97-23)			5. FUNDING NUMBERS	
6. AUTHORS T. Sutherland				
7. PERFORMING ORGANIZATION NAMES(S) AND ADDRESS(ES) George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812			8. PERFORMING ORGANIZATION REPORT NUMBER M-956	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/TM--1999-209788	
11. SUPPLEMENTARY NOTES Prepared by Avionics Department Engineering Directorate				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 33 Nonstandard Distribution			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A video guidance sensor (VGS) system has flown on both STS-87 and STS-95 to validate a single camera/target concept for vehicle navigation. The main part of the image algorithm was the subtraction of two consecutive images using software. For a nominal size image of 256 x 256 pixels this subtraction can take a large portion of the time between successive frames in standard rate video, leaving very little time for other computations. The purpose of this project was to integrate the software subtraction into hardware to speed up the subtraction process and allow for more complex algorithms to be performed, both in hardware and software.				
14. SUBJECT TERMS image subtraction, algorithm, vehicle navigation, STS-87, STS-95, VGS			15. NUMBER OF PAGES 16	
			16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited	